

GENERAC®

MOBILE

GLT4 DC Hyper

GLT SERIES – LIGHTING TOWER



Hyper LED
system



Long operating
time



Great
maneuverability



DC voltage
alternator

- 4x 45000Lm Hyper LED
- Hydraulic lifting system
- 2-cyl. diesel engine
- Road trailer



GLT4 DC Hyper

Innovation comes through a careful management of space. The **GLT4 DC lighting tower** features exclusive **Hyper LED floodlights** and a **DC voltage alternator**, combining all market requirements inside a very compact frame.

MAIN FEATURES

- 4x 45000Lm low-voltage floodlights
- Multi-rotating Hyper LED system with optional anti-glare shells
- Low voltage alternator (48V DC)
- Hydraulic mast lifting system
- Compact shape with “seagull-wing” doors for an easy access to the built-in generator
- Low-consumption engine (2 cylinders)
- Road trailer with long, foldable drawbar to optimize transport
- DSE L401-MKII digital controller
- Plastic fuel tank with liquid containment



Technical data

Minimum dimensions (L x W x H)	2156 x 1400 x 2505 mm
Maximum dimensions (L x W x H)	3096 x 2166 x 8300 mm
Dry weight	935 kg
LED floodlights	4x 45000 Lm
Total luminous flux	180000 Lm
Floodlights efficiency	175 Lm/W
Illuminated area (1 lux min.)	10700 m ²
Alternator	1.4 kVA 48 V DC
Engine model	Kubota Z482
Engine speed	1500 RPM
Cylinder number	2
Engine cooling	Liquid
Average sound pressure level	60 dB(A) @ 7 m
Running time	257 h
Fuel tank capacity (gross / net)	200 / 180 l
Liquid containment tank	Yes
Mast lifting system	Hydraulic
Mast rotation	340°
Wind resistance	110 km/h