

GENERAC®

MOBILE

GLT6-A

GLT SERIES - LIGHTING TOWER



High illuminating
capacity



Long operating
time



Great
maneuverability



Wide
accessibility

- 6x 320W LED
- Hydraulic lifting system
- 3-cyl. diesel engine
- Road trailer



GLT6-A

Innovation comes through a careful management of space. The **GLT6-A lighting tower** combines all market requirements inside a very compact frame.

MAIN FEATURES

- 6x 320W LED floodlights
- Hydraulic lifting system
- Compact shape with “seagull-wing” doors for an easy access to the built-in generator
- Low-consumption engine (3 cylinders)
- Road trailer with long, foldable drawbar to optimize transport
- DSE L401-MKII digital controller
- 2x outlet electric sockets (16A)
- Inlet electric plug (16A)
- Plastic fuel tank with liquid containment



Technical data

Minimum dimensions (L x W x H)	2156 x 1400 x 2403 mm
Maximum dimensions (L x W x H)	3095 x 2166 x 8387 mm
Dry weight	1000 kg
LED floodlights	6x 320W
Luminous flux	276000 Lm
Illuminated area (1 lux min.)	12600 m ²
Alternator (50 / 60 Hz)	8 kVA 230 V / 8 kVA 240 V
Frequency	50 / 60 Hz
Engine model	Kubota D1105
Engine speed (50 / 60 Hz)	1500 / 1800 RPM
Cylinder number	3
Engine cooling	Liquid
Average sound pressure level	63 dB(A) @ 7m
Running time	140 h
Fuel tank capacity (gross / net)	200 / 180 l
Liquid containment tank	Yes
16A single-phase inlet plug	1
16A single-phase outlet socket	2
Mast lifting system	Hydraulic
Mast rotation	340°
Wind resistance	110 km/h